



1. PRODUCT NAME

**Shadows Collection
Data Sheet - SP 17-0728 REV00**

2. MANUFACTURER

Stonepeak Ceramics, Inc.
 314 West Superior, Suite 201
 Chicago, IL 60654
 Telephone: 312.506.2800
 Fax: 312.335.0533
 Email: info@stonepeakceramics.com
 Website: www.stonepeakceramics.com

3. PRODUCT DESCRIPTION

Shadows Collection - Stunning wall tile offered in both matte and glossy. Available in eight harmonious colors to complement most other Stonepeak collections with bullnose option.

Recommended Applications:

Ideally suited for wall.

Finishes/Textures:

Glossy / Matte - Glazed

Size/thickness:

4" x 12" x 3/11" nominal *(7 mm)

**denotes work size per ISO 10545-2*

Recommended Grout Joint: 3/32" or greater
All sizes modular with 3/16" grout joint (≈5 mm)

Grout joints of 1/8" inch or less, especially with larger format tiles or running bond patterns, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.

For patterns with running bond/brick joints patterns StonePeak recommends a maximum of 33% offset.

Stonepeak Ceramics Trim System

Bullnose trim is available for complete design aesthetics.

Refer to **StonePeak Ceramics Product Catalog or Website**

4. TECHNICAL DATA

Physical Properties	ASTM Test	Industry Standards	SP Results
Water Absorption	C373	P4	P4
Thickness Dimension	C499	Range ± 0.04 Inc. Max	≤± 0.04 Inch
Facial Dimension	C499	± 0.25%	≤± 0.25%
Warpage Average diagonal	C485	Range- 0.30% / +0.40%	≤-0.30 % / + 0.40%
Warpage Average edge	C485	Range- 0.30% / +0.40%	≤-0.30 % / +0.40%
Wedging	C502	± 0.25%	≤± 0.25%
Bond Strength	C482	≥ 50 psi	≥ 200 psi
Breaking Strength	C648	≥250 lbf	≥ 250 lbf
Visible Abrasion Resistance for Glazed tiles	C1027	No Requirement Range 0 - 5	Class 3
Chemical Resistance	C650	No Requirement Range E - A	Unaffected/ Class A
Stain Resistance	C1378	No Requirement Range E - A	Class A*
Aesthetic Class/Shade Rating	Visual Evaluation Shade & Texture	No Requirement Range V0 - V4	V2

COF: all values given are for matte or honed material. No values are given for polished material. StonePeak does not recommend polished surfaces in areas subject to exposure from grease, oil or water.

5. INSTALLATION

Surface preparations:

All installation work using StonePeak Ceramics tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCA Handbook for Ceramic Tile installations.

All substrates should be between 40 degrees F and 90 degrees F and structurally sound, clean and free of all dirt, oil, grease, paint, concrete sealers or curing compounds as per ANSI A108.01.

Deflection:

Substrate must conform to all state and local building code requirements and ANSI A108.01 for maximum allowable substrate deflection

Movement Joints:

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01- 3.7; A108.02 – 4.4.and TCA Details EJ171.

Installation or setting materials:

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.

6. AVAILABILITY AND COST

StonePeak Shadows Collection is available from select distributors of ceramic tile and stone.

To find accessible information of delivery and product costs for your area, please contact your nearest StonePeak Ceramics distributor.

See section 2 for contact information.

7. WARRANTY

StonePeak Ceramics guarantees that its products will be free of manufacturing defects and they will meet or exceed the performance specifications set forth in ANSI 137.1.

For further information and details please contact your nearest StonePeak Ceramics Distributor for a written copy of the warranty information.

8. MAINTENANCE

Care and Maintenance Recommendations

Please refer to **StonePeak Ceramics Care and Maintenance Recommendations Guide** for all technical information as to the care of this collection.

9. TECHNICAL SERVICES

Technical Assistance

Guide Specifications, literature, MSDS, tile samples, details and installation procedures are all available for your use or libraries.

Please contact your nearest StonePeak distributor for catalogues or physical samples.

Continued Education Programs are available – **1 or 2 hour HSW Learning Units** – contact StonePeak Ceramics' main office to set up a presentation.

10. FILING SYSTEMS

[Shadows Collection](#)

White Matte & Glossy



Black Matte & Glossy




Ashgrey Matte & Glossy



Smoke Matte & Glossy



Deepgrey Matte & Glossy



Almond Matte & Glossy



Brown Matte & Glossy



Taupe Matte & Glossy



Note to Specifier: Click on color with Internet Connection to hyperlink directly to product color data at the StonePeak Ceramics website.